

Docket No.: YOR920000210US2

IN THE CLAIMS:

Please amend the claims as indicated below.

Please cancel claims 8, 41, 53 and 58, without prejudice.

5

1. (Currently Amended) A method comprising the steps of:
creating an evaluation model from at least one evaluation phone;
creating a synthesizer model from at least one synthesizer phone; and
determining a matrix from the evaluation and synthesizer models, said
10 matrix configured for speech recognition;
creating a new matrix by subtracting the matrix from an identity matrix.
determining an inverse of the new matrix; and
determining acoustic confusability by using the inverse of the new matrix.

15

2. (Original) The method of claim 1:
wherein the at least one evaluation phone comprises a first plurality of
evaluation phones, the at least one synthesizer phone comprises a first plurality of
synthesizer phones; and
wherein the method further comprises the steps of:
20 creating a new matrix by subtracting the matrix from an identity matrix;
creating an intermediate matrix comprising the new matrix and a second
identity matrix;
determining a first set of specific elements of the intermediate matrix; and
determining acoustic confusability from one of the specific elements.

25

3. (Original) The method of claim 2, further comprising the steps of:
creating a second evaluation model comprising the first plurality of
evaluation phones and additional evaluation phones;
creating a second matrix from the second evaluation model and the
30 synthesizer model;

Docket No.: YOR920000210US2

creating a second new matrix by subtracting the second matrix from a third identity matrix;

creating a second intermediate matrix comprising the second new matrix and a fourth identity matrix;

5 determining a second set of specific elements of the intermediate matrix, the specific elements corresponding to a column of the second intermediate matrix, wherein the second set of specific elements comprise the first set of specific elements and a new set of specific elements; and

10 determining a second acoustic confusability by using previously performed calculations of the first set of elements and by calculating the new set of specific elements.

4. (Original) The method of claim 1, wherein the evaluation model comprises a hidden Markov model of the at least one evaluation phone and wherein the synthesizer model comprises a hidden Markov model of the at least one synthesizer phone.

5. (Original) The method of claim 4, wherein at least one of the hidden Markov models comprises a plurality of states and a plurality of transitions between states, wherein at least one of the transitions is a transition from one of the states to itself, wherein at least one of the transitions is a transition from one of the states to another of the states, wherein each transition has a transition probability associated with it, and wherein each state has a probability density associated with it.

25 6. (Original) The method of claim 5, wherein the plurality of states comprises a starting state, an ending state and an intermediate state, wherein the plurality of transitions comprise:

30 a transition from the starting state to itself;
a transition from the starting state to the intermediate state;
a transition from the intermediate state to itself;
a transition from the intermediate state to the ending state; and

Docket No.: YOR920000210US2

a transition from the ending state to itself.

7. (Original) The method of claim 1, further comprising the steps of:
creating a new matrix by subtracting the matrix from an identity matrix;
5 determining an inverse of the new matrix by the following steps:
creating an intermediate matrix comprising the new matrix and a second
identity matrix;
determining a specific entry of the second identity matrix that corresponds
to acoustic confusability;
10 determining a specific column or row in which the specific entry resides;
and
performing column or row manipulations to create a third identity matrix
in the new matrix while calculating only entries of the specific column or row in the
second identity matrix; and
15 selecting the specific entry as the acoustic confusability.
8. (Cancelled).
9. (Currently Amended) The method of claim 8~~1~~, wherein the step of
20 determining acoustic confusability by using the inverse of the new matrix comprises the
step of selecting one element of the inverse of the new matrix as the acoustic
confusability.
10. (Currently Amended) The method of claim 5~~1~~, wherein the step of
25 determining a matrix from the evaluation and synthesizer models comprises the steps of:
determining a plurality of product machine states; and
determining a plurality of product machine transitions between the product
machine states.
- 30 11. (Original) The method of claim 10, wherein:

Docket No.: YOR920000210US2

each of the product machine states corresponds to one of the states of the evaluation model and one of the states of the synthesizer model;

each of the product machine transitions connects one of the product machine states to the same or another product machine state; and

5 a product machine transition exists when one or both of the following are true: a transition connects one evaluation model state with the same or another evaluation model state and a transition connects one synthesizer model state with the same or another synthesizer model state.

10 12. (Original) The method of claim 10, wherein the step of determining a matrix from the evaluation and synthesizer models further comprises the steps of:

determining a product machine transition probability for each of the plurality of product machine transitions; and

determining a synthetic likelihood for each of the product machine states.

15

13. (Original) The method of claim 10, wherein the matrix comprises a plurality of elements and wherein each element of the matrix corresponds to a potential transition between two of the product machine states.

20 14. (Original) The method of claim 13, wherein the step of determining a matrix from the evaluation and synthesizer models further comprises the steps of:

selecting an element of the matrix;

assigning a probability to the element if a product machine transition exists between two product machine states corresponding to a potential transition that
25 corresponds to the element, else assigning a zero to the element; and

continuing the steps of selecting and assigning until each element of the matrix has been assigned.

15. (Previously Presented) A method comprising the steps of:

30 a) creating an evaluation model from a plurality of evaluation phones, each of the phones corresponding to a first word;

Docket No.: YOR920000210US2

- b) creating a synthesizer model from a plurality of synthesizer phones, each of the phones corresponding to a second word;
- c) creating a product machine from the evaluation model and synthesizer model, the product machine comprising a plurality of transitions and a plurality of states;
- 5 d) determining a matrix from the product machine; and
- e) determining acoustic confusability of the first word and the second word by using the matrix, said matrix configured for speech recognition.
- 10 16. (Original) The method of claim 15, wherein each of the evaluation and synthesizer models comprises a hidden Markov model.
17. (Original) The method of claim 16, further comprising the step of determining synthetic likelihoods for each of the plurality of product machine states.
- 15 18. (Original) The method of claim 17, wherein each synthetic likelihood is a measure of the acoustic confusability of two specific observation densities associated with the hidden Markov models of the evaluation and synthesizer models.
- 20 19. (Original) The method of claim 17, wherein the synthetic likelihoods are compressed by normalization.
20. (Original) The method of claim 17, wherein the synthetic likelihoods are compressed by ranking.
- 25 21. (Original) The method of claim 17, wherein all synthetic likelihoods are determined through a method selected from the group consisting essentially of a cross-entropy measure, a dominance measure, a decoder measure, and an empirical measure.

Docket No.: YOR920000210US2

22. (Original) The method of claim 15, further comprising the steps of:

f) performing steps (a) through (e) for a plurality of word pairs, each word pair comprising evaluation and synthesizer models, thereby determining a plurality of acoustic confusabilities; and

5 g) determining acoustic perplexity by using the plurality of acoustic confusabilities.

23. (Original) The method of claim 15 further comprising the steps of:

10 f) performing steps (a) through (e) for a plurality of word pairs, each word pair comprising evaluation and synthesizer models, thereby determining a plurality of acoustic confusabilities; and

g) determining synthetic acoustic word error rate by using the plurality of acoustic confusabilities.

15 24. (Currently Amended) A method comprising the steps of:

a) determining acoustic confusability for each of a plurality of word pairs, wherein step (a) further comprises the steps of, for each of the word pairs:

determining an edit distance between each word of the word pair; and

determining acoustic confusability from the edit distance; and

20 b) determining a metric by using the acoustic confusabilities, wherein step (b) further comprises the step of determining an acoustic perplexity by using the confusabilities.

25 25. (Cancelled)

26. (Previously Presented) The method of claim 24 ~~25~~, further comprising the steps of:

c) performing steps (a) and (b) to determine an acoustic perplexity of a basic bigram language model;

30 d) performing steps (a) and (b) to determine an acoustic perplexity of an augmented language model; and

Docket No.: YOR920000210US2

e) determining gain comprising a logarithm of a fraction determined by dividing the acoustic perplexity of the augmented language model by the acoustic perplexity of the base bigram language model.

5 27. (Previously Presented) The method of claim 24, further comprising the step of:

c) minimizing acoustic perplexity during training of a language model.

10 28. (Original) The method of claim 27, wherein step (c) further comprises the step of maximizing a negative logarithm of the acoustic perplexity.

29. (Original) The method of claim 24, wherein step (b) further comprises the step of determining a Synthetic Acoustic Word Error Rate (SAWER) by using the
15 confusabilities.

30. (Original) The method of claim 29, further comprising the steps of:

c) performing steps (a) and (b) to determine a SAWER of a base bigram language model;

20 d) performing steps (a) and (b) to determine a SAWER of an augmented language model; and

e) determining an improvement comprising a difference between the SAWER of the augmented language model and the SAWER of the base bigram language model.

25

31. (Original) The method of claim 29, further comprising the step of:

c) minimizing the SAWER during training of a language model.

32. (Original) The method of claim 31, wherein step (c) further comprises the
30 step of maximizing one minus the SAWER.

Docket No.: YOR920000210US2

33. (Original) The method of claim 29, further comprising the steps of:
- c) performing steps (a) and (b) to determine a SAWER for a vocabulary;
 - d) augmenting the vocabulary with at least one additional word;
 - 5 e) performing steps (a) and (b) to determine a SAWER for the augmented vocabulary; and
 - f) determining an improvement comprising a difference between the SAWER for the vocabulary and the SAWER for the augmented vocabulary.
- 10 34. (Original) The method of claim 33, further comprising the steps of:
- g) performing steps (d) through (f) for a plurality of additional words;
 - h) determining a particular word of the additional words that has the best improvement; and
 - i) adding the particular word to the vocabulary.
- 15 35. (Original) The method of claim 24, wherein each of the words of the word pairs is represented by a hidden Markov model, and wherein step (a) further comprises the steps of:
- creating a product machine for each of the plurality of word pairs, wherein
 - 20 each word each product machine comprising a plurality of states and a plurality of transitions determined by the hidden Markov models of a corresponding word pair; and
 - for each product machine, determining synthetic likelihoods for each of the plurality of product machine states.
- 25 36. (Original) The method of claim 35, wherein each synthetic likelihood is a measure of the acoustic confusability of two specific observation densities associated with the hidden Markov models of the corresponding word pair.
37. (Original) The method of claim 35, wherein the synthetic likelihoods are
- 30 compressed by normalization.

Docket No.: YOR920000210US2

38. (Original) The method of claim 35, wherein the synthetic likelihoods are compressed by ranking.

39. (Original) The method of claim 35, wherein all synthetic likelihoods are
5 determined through a method selected from the group consisting essentially of a cross-entropy measure, a dominance measure, a decoder measure, and an empirical measure.

40. (Original) The method of claim 35:
wherein step (a) further comprises the step of, for each acoustic
10 confusability:
determining a matrix from a corresponding product machine; and
determining an inverse of a second matrix created by subtracting the
matrix from an identity matrix; and
wherein each hidden Markov model comprises a plurality of phones;
15 wherein a larger word and a smaller word have an identical sequence of
phones;
wherein the larger of the two words comprises an additional set of phones;
and
wherein a set of calculations performed when determining the inverse of
20 the matrix for the smaller word is cached and used again when determining the inverse of
the matrix for the larger word.

41. (Cancelled).

25 42. (Currently Amended) The method of claim ~~41~~24, wherein the edit distance is determined by determining a number of operations and a type of each operation to change one word of the word pair into the other word of the word pair.

43. (Original) The method of claim 42, wherein the operations are selected
30 from the group consisting essentially of deletions, substitutions and additions of phones.

Docket No.: YOR920000210US2

44. (Original) The method of claim 42, further comprising the step of weighting each operation.

45. (Original) The method of claim 42, further comprising the step of
5 assigning a cost to each operation.

46. (Previously Presented) A method for determining acoustic confusability of a word pair, the method comprising the steps of:
determining an edit distance between each word pair and an associated
10 alignment;
assigning acoustic distances to each aligned phoneme pair; and
determining an acoustic confusability by summing said acoustic distances.

47. (Original) The method of claim 46, wherein the edit distance is determined
15 by determining a number of operations and a type of each operation to change one word of the word pair into the other word of the word pair.

48. (Original) The method of claim 47, wherein the operations are selected from the group consisting essentially of deletions, substitutions and additions of phones.
20

49. (Original) The method of claim 47, further comprising the step of weighting each operation.

50. (Original) The method of claim 47, further comprising the step of
25 assigning a cost to each operation.

51. (Currently Amended) An apparatus comprising:
a memory that stores computer-readable code; and
a processor operatively coupled to said memory, said processor configured
30 to implement said computer-readable code, said computer-readable code configured to:
create ~~creating~~ an evaluation model from at least one evaluation phone;

Docket No.: YOR920000210US2

~~create~~ ~~creating~~ a synthesizer model from at least one synthesizer phone;
and

~~determine~~ ~~determining~~ a matrix from the evaluation and synthesizer
models;

5 ~~create a new matrix by subtracting the matrix from an identity matrix.~~
 ~~determine an inverse of the new matrix; and~~
 ~~determine acoustic confusability by using the inverse of the new matrix.~~

52. (Currently Amended) An apparatus comprising:
10 a memory that stores computer-readable code; and
 a processor operatively coupled to said memory, said processor configured
to implement said computer-readable code, said computer-readable code configured to:
 a) determine acoustic confusability for each of a plurality of word
pairs, wherein step (a) further comprises the steps of, for each of the word pairs:
15 determining an edit distance between each word of the word pair; and
 determining acoustic confusability from the edit distance; and
 b) determine a metric by using the acoustic confusabilities, wherein
step (b) further comprises the step of determining an acoustic perplexity by using the
confusabilities.

20

53. (Cancelled).

54. (Previously Presented) The apparatus of claim 52, wherein the computer-
readable code is further configured, when performing step (b), to determine a Synthetic
25 Acoustic Word Error Rate (SAWER) by using the confusabilities.

55. (Previously Presented) An apparatus for determining acoustic
confusability of a word pair, the system comprising:
 a memory that stores computer-readable code; and
30 a processor operatively coupled to said memory, said processor configured
to implement said computer-readable code, said computer-readable code configured to:

Docket No.: YOR920000210US2

determine an edit distance between each word pair and an associated alignment;

assign acoustic distances to each aligned phoneme pair; and

determine an acoustic confusability by summing said acoustic distances.

5

56. (Currently Amended) An article of manufacture comprising:

a computer-readable medium having computer-readable code means embodied thereon, the computer-readable program code means comprising:

a step to creating an evaluation model from at least one evaluation phone;

10

a step to creating a synthesizer model from at least one synthesizer phone;

and

a step to determining a matrix from the evaluation and synthesizer models;

a step to create a new matrix by subtracting the matrix from an identity matrix.

15

a step to determine an inverse of the new matrix; and

a step to determine acoustic confusability by using the inverse of the new matrix.

57. (Currently Amended) An article of manufacture comprising:

20

a computer-readable medium having computer-readable code means embodied thereon, the computer-readable program code means comprising:

a) a step to determine acoustic confusability for each of a plurality of word pairs, wherein step (a) further comprises the steps of, for each of the word pairs:

determining an edit distance between each word of the word pair; and

25

determining acoustic confusability from the edit distance; and

b) a step to determine a metric by using the acoustic confusabilities, wherein step (b) further comprises the step of determining an acoustic perplexity by using the confusabilities.

30

58. (Cancelled).

Docket No.: YOR920000210US2

59. (Original) The article of manufacture of claim 57, wherein the computer-readable program code means further comprises, when performing step (b), a step to determine a Synthetic Acoustic Word Error Rate (SAWER) by using the confusabilities.

5 60. (Previously Presented) An article of manufacture for determining acoustic confusability of a word pair, the article of manufacture comprising:

a computer-readable medium having computer-readable code means embodied thereon, the computer-readable program code means comprising:

10 alignment;
determine an edit distance between each word pair and an associated

assign acoustic distances to each aligned phoneme pair; and

determine an acoustic confusability by summing said acoustic distances.